

TPWLKI

TPWLKI SERIES STAINLESS STEEL PALLET TRUCK SCALE



Stainless steel pallet truck scales with built-in multirange electronic weighing, easy to use. Weight detection with four IP68 stainless steel load cells. Sturdy structure suitable for harsh work conditions. Manufactured, calibrated and adjusted in Italy by Dini Argeo, using certified sample masses. Available also CE-M APPROVED.

Working in cooperation with:

SCALEIT AS

VESTVOLLVEIEN 30B - 2019 - SKEDSMOKORSET - NORWAY
Tel. 0047 64836750 Fax. 0047 63872590
post@scaleit.no www.scaleit.no

**The best solution
for advanced industrial
applications**

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy: +/- 0.05% of the maximum capacity.
- Fork dimensions 1180 x 550 x 80 mm. Weighs about 135 kg.
- Bearing structure in extra thick STAINLESS steel.
- Lifting pump in STAINLESS steel.
- Steering wheels and double loading rollers in nylon.
- Closed forks, for a higher protection of the double loading wheels.
- 4 IP68 stainless steel shear beam load cells.
- IP65 stainless steel weight indicator, easy to clean and resistant to harsh and corrosive environments; large 25mm backlit LCD display, clearly visible also in poor lighting conditions.
- Calibration and Set-Up from keyboard or from PC.
- Power supply through built-in rechargeable battery.
- 80-hour approximate operating time or one month with the typical non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Low battery warning.
- Equipped with 230Vac 50 Hz battery charger.
- Bi-directional RS232/C port for connection to printer.
- Bi-directional RS232/C port for PC, radio modem, or portable terminal.
- IR input for managing the remote control.
- Fitted with thermal printer in the TPWLKIP and TPWLKIPM versions.

AVAILABLE UPON PRICE ESTIMATE

- Special capacity e/o divisions.
- High resolution.

MAIN FUNCTIONS

- The user can select the operating modes directly using the dedicated key*:
 - High resolution display x 10
 - Precision weighing with temporary recalibration via a sample weight (for internal factory use)
 - Net/Gross
 - Lb to Kg converter
 - Free conversion factor (for meter and litre counters etc.)
 - Weight totalizer
 - Formulizer
 - +/- controller with quick target and threshold input
 - Percentage weighing
 - Percentage batching with programmable target
 - Piece counter
 - Hold
 - Alibi memory (optional)
- Access to the user menu is gained using the dedicated key* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.

* These quick access keys to the menus can be blocked by configuring a dedicated password.

DETAIL 1



DETAIL 2



Standard printer with dedicated RS232/C bidirectional port (TPWLKIP and TPWLKIPM versions).

VERSIONS

Available versions

Codice	Max (kg)	d (kg)	M (kg)
TPWLKI-2	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPWLKIM-2 M	1000 / 2000	--	0,5 / 1
TPWLKIP-2	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPWLKIPM-2 M	1000 / 2000	--	0,5 / 1



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano - Modena - Italy
Tel. +39.0536 843418

SCALEIT AS

VESTVOLLVEIEN 30B - 2019 - SKEDSMOKORSET - NORWAY

Tel. 0047 64836750 Fax. 0047 63872590

post@scaleit.no www.scaleit.no

SALES AND TECHNICAL ASSISTANCE SERVICE