



Stand scale

9965

- ▶ Extra low-profile, ergonomic stainless steel platform; weighed goods only need to be lifted minimally
- ▶ Protection Class IP 42
- ▶ Weight units switchable between kg and lb
- ▶ 5-key operation with freely assignable F key
- ▶ Energy-efficient due to integrated Auto-off function



Features

- ▶ Extra low-profile, ergonomic stainless steel platform; weighed goods only need to be lifted minimally
- ▶ Separate display unit – weighed goods do not conceal the display
- ▶ Large LC display, character height: 25 mm
- ▶ 5-key operation with freely assignable F key
- ▶ Integrated USB interface type B (virtual serial interface)
- ▶ Flexible use at different locations due to battery operation (6x AA batteries) or optional battery operation with battery pack and charging circuit (battery life approx. 50 hrs., depending on settings)
- ▶ Energy-efficient due to integrated Auto-off function of the rechargeable battery with adjustable timer from 1 – 30 minutes or continuous operation
- ▶ Mains operation: 100 – 240 V / 50 – 60 Hz UK or US adapter, see accessories
- ▶ Fast and stable standstill behaviour (filter type 3)
- ▶ Internal user calibration for location-specific adjustments
- ▶ Weight units switchable between kg and lb
- ▶ Functions: Weighing, tare, plus/minus weighing, add, hold, user filter setting, EDP for selection of 5 variants of data sets, auto tare
- ▶ Weighing platform: Stainless steel 1.4301,
Base frame: Painted or galvanized sheetmetal
- ▶ Protection Class IP 42
- ▶ Nominal operating temperature: -10 °C to 40 °C
- ▶ Scale dimensions / scale weight:
310 x 400 x 520 mm, 5 kg

All interfaces have factory-preset print images and EDP data records for direct data output and data communication. These can also be individually adapted via the service programme 25641.10.001 (see accessories).

Products

Order number Variation	Approvable	Division g	Maximum load kg	Model substructure	Platform size mm	Protection class
9965.01.001 Stand scale	No	5	15	Galvanized steel sheet	310 x 275 x 35	IP 42
9965.01.002 Stand scale incl. accu	No	5	15	Galvanized steel sheet	310 x 275 x 35	IP 42
9965.02.001 Stand scale	No	10	30	Galvanized steel sheet	310 x 275 x 35	IP 42
9965.02.002 Stand scale incl. accu	No	10	30	Galvanized steel sheet	310 x 275 x 35	IP 42
9965.03.001 Stand scale	No	20	60	Galvanized steel sheet	310 x 275 x 35	IP 42
9965.03.002 Stand scale incl. accu	No	20	60	Galvanized steel sheet	310 x 275 x 35	IP 42

Accessories

Order number Variation	Description
2550.03.022	USB 2.0 cable 3 m with 2 plugs A-plug, B-plug, for IP 42 version (for integrated virtual serial USB interface and keyboard wedge)
2564.20.002	Scale Connecting , software for transferring scale data to PC based software
2564.20.005	Scale Connecting Plus, extensive software for transferring scale data to PC-based software (with activation code)
2564.20.006	Software for linking scale to SAP R/3, single-user solution for SAP GUI via RS 232, USB or Ethernet
2557.40.005	Battery incl. charging circuit installed for mains-free operation Option must be included in the purchase order. Retrofits are not possible
2557.25.002	UK power adapter
2557.25.004	US power adapter