



More information on the website  
[radwag.com/en/info,w1,4KI](http://radwag.com/en/info,w1,4KI)

MA 210.5Y.IC.WH Moisture Analyzer, MA 110.5Y.IC Moisture Analyzer, MA 50.5Y.IC.WH Moisture Analyzer, MA 50/1.5Y.IC.NS Moisture Analyzer, MA 210.5Y.IC Moisture Analyzer, MA 200/1.5Y.IC.NS Moisture Analyzer, MA 200/1.5Y.IC.WH Moisture Analyzer, MA 50.5Y.IC.NS Moisture Analyzer, MA 50/1.5Y.IC.WH Moisture Analyzer, MA 50.5Y.IC Moisture Analyzer, MA 50/1.5Y.IC Moisture Analyzer, MA 110.5Y.IC.WH Moisture Analyzer, MA 210.5Y.IC.NS Moisture Analyzer, MA 110.5Y.IC.NS Moisture Analyzer, MA 200/1.5Y.IC Moisture Analyzer



MA 210.5Y.IC.WH Moisture Analyzer  
 MA 110.5Y.IC Moisture Analyzer  
 MA 50.5Y.IC.WH Moisture Analyzer  
 MA 50/1.5Y.IC.NS Moisture Analyzer  
 MA 210.5Y.IC Moisture Analyzer  
 MA 200/1.5Y.IC.NS Moisture Analyzer  
 MA 200/1.5Y.IC.WH Moisture Analyzer  
 MA 50.5Y.IC.NS Moisture Analyzer  
 MA 50/1.5Y.IC.WH Moisture Analyzer  
 MA 50.5Y.IC Moisture Analyzer  
 MA 50/1.5Y.IC Moisture Analyzer  
 MA 110.5Y.IC.WH Moisture Analyzer  
 MA 210.5Y.IC.NS Moisture Analyzer  
 MA 110.5Y.IC.NS Moisture Analyzer  
 MA 200/1.5Y.IC Moisture Analyzer

The drawings, photos and graphics used are for illustrative purposes only.

## Functions



Autotest



Statistics



IR sensors



GLP Procedures



Replaceable unit



Statistical Quality Control



ALIBI Memory



Drying modes



Samples drying



Moisture content analysis



Dry mass determination



Wi-Fi

# Datasheet

	MA 50/1.5Y.IC.NS Moisture Analyzer	MA 50.5Y.IC.NS Moisture Analyzer	MA 50/1.5Y.IC.WH Moisture Analyzer
<b>Metrological parameters</b>			
Maximum capacity [Max]	50 g	50 g	50 g
Readability [d]	0,1 mg	1 mg	0,1 mg
Tare range	-50 g	-50 g	-50 g
Adjustment	internal (automatic)	internal (automatic)	internal (automatic)
Maximum sample weight	50 g	50 g	50 g
Heating module	metal heater	metal heater	halogen
Moisture content repeatability	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)
Moisture content readability	0,0001%	0,001%	0,0001%
Drying temperature range	Max 160 °C	Max 160 °C	Max 250 °C
<b>Physical parameters</b>			
Leveling system	semi-automatic - LevelSENSING	semi-automatic - LevelSENSING	semi-automatic - LevelSENSING
Display	10" graphic colour touchscreen	10" graphic colour touchscreen	10" graphic colour touchscreen
Weighing chamber	automatic	automatic	automatic
Maximum sample height	20 mm	20 mm	20 mm
Weighing pan dimensions	ø90, h= 8 mm	ø90, h= 8 mm	ø90, h= 8 mm
Packaging dimensions	540x610x470 mm	540x610x470 mm	540x610x470 mm
Net weight	5,3 kg	5,3 kg	5,3 kg
Gross weight	6,8 kg	6,8 kg	7 kg
<b>Construction</b>			
Protection class	IP 43	IP 43	IP 43
<b>Features of use</b>			
Display mode	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC
Drying method	4 drying profiles (standard, fast, step, mild)	4 drying profiles (standard, fast, step, mild)	4 drying profiles (standard, fast, step, mild)
Finish mode	4 modes (automatic, manual, time-defined, user-defined)	4 modes (automatic, manual, time-defined, user-defined)	4 modes (automatic, manual, time-defined, user-defined)
Additional functions	sample traceability	sample traceability	sample traceability
<b>Communication interface</b>			
Communication interface	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
<b>Electrical parameters</b>			
Power supply	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz
Power consumption	6 W	6 W	6 W
Heating module power	450 W	450 W	450 W
<b>Environmental conditions</b>			
Operating temperature	+10 ÷ +40 °C	+10 ÷ +40 °C	+10 ÷ +40 °C
<b>SOP – metrological tests</b>			
Mass indication control	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)
Internal adjustment	For .IC models only, GLP report	For .IC models only, GLP report	For .IC models only, GLP report
External adjustment	For all models, GLP report	For all models, GLP report	For all models, GLP report
Drying temperature control	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)
Moisture content indication control	Certified MV Test Set	Certified MV Test Set	Certified MV Test Set
<b>Adjustment</b>			
Internal / External adjustment	Depending on the type of moisture analyzer, GLP report	Depending on the type of moisture analyzer, GLP report	Depending on the type of moisture analyzer, GLP report

1 Barcode scanners, available as weighing instrument accessory, communicate with the instrument via RS232 interface exclusively.

# Datasheet

	MA 50.5Y.IC.WH Moisture Analyzer	MA 50/1.5Y.IC Moisture Analyzer	MA 50.5Y.IC Moisture Analyzer
<b>Metrological parameters</b>			
Maximum capacity [Max]	50 g	50 g	50 g
Readability [d]	1 mg	0,1 mg	1 mg
Tare range	-50 g	-50 g	-50 g
Adjustment	internal (automatic)	internal (automatic)	internal (automatic)
Maximum sample weight	50 g	50 g	50 g
Heating module	halogen	IR emitter	IR emitter
Moisture content repeatability	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)
Moisture content readability	0,001%	0,0001%	0,001%
Drying temperature range	Max 250 °C	Max 160 °C	Max 160 °C
<b>Physical parameters</b>			
Leveling system	semi-automatic - LevelSENSING	semi-automatic - LevelSENSING	semi-automatic - LevelSENSING
Display	10" graphic colour touchscreen	10" graphic colour touchscreen	10" graphic colour touchscreen
Weighing chamber	automatic	automatic	automatic
Maximum sample height	20 mm	20 mm	20 mm
Weighing pan dimensions	ø90, h= 8 mm	ø90, h= 8 mm	ø90, h= 8 mm
Packaging dimensions	540x610x470 mm	540x610x470 mm	540x610x470 mm
Net weight	5,3 kg	5,3 kg	5,3 kg
Gross weight	6,8 kg	6,8 kg	6,5 kg
<b>Construction</b>			
Protection class	IP 43	IP 43	IP 43
<b>Features of use</b>			
Display mode	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC
Drying method	4 drying profiles (standard, fast, step, mild)	4 drying profiles (standard, fast, step, mild)	4 drying profiles (standard, fast, step, mild)
Finish mode	4 modes (automatic, manual, time-defined, user-defined)	4 modes (automatic, manual, time-defined, user-defined)	4 modes (automatic, manual, time-defined, user-defined)
Additional functions	sample traceability	sample traceability	sample traceability
<b>Communication interface</b>			
Communication interface	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
<b>Electrical parameters</b>			
Power supply	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz
Power consumption	6 W	6 W	6 W
Heating module power	450 W	450 W	450 W
<b>Environmental conditions</b>			
Operating temperature	+10 ÷ +40 °C	+10 ÷ +40 °C	+10 ÷ +40 °C
<b>SOP – metrological tests</b>			
Mass indication control	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)
Internal adjustment	For .IC models only, GLP report	For .IC models only, GLP report	For .IC models only, GLP report
External adjustment	For all models, GLP report	For all models, GLP report	For all models, GLP report
Drying temperature control	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)
Moisture content indication control	Certified MV Test Set	Certified MV Test Set	Certified MV Test Set
<b>Adjustment</b>			
Internal / External adjustment	Depending on the type of moisture analyzer, GLP report	Depending on the type of moisture analyzer, GLP report	Depending on the type of moisture analyzer, GLP report

1 Barcode scanners, available as weighing instrument accessory, communicate with the instrument via RS232 interface exclusively.

# Datasheet

	MA 110.5Y.IC Moisture Analyzer	MA 110.5Y.IC.NS Moisture Analyzer	MA 110.5Y.IC.WH Moisture Analyzer
<b>Metrological parameters</b>			
Maximum capacity [Max]	110 g	110 g	110 g
Readability [d]	1 mg	1 mg	1 mg
Tare range	-110 g	-110 g	-110 g
Adjustment	internal (automatic)	internal (automatic)	internal (automatic)
Maximum sample weight	110 g	110 g	110 g
Heating module	IR emitter	steel heater	halogen
Moisture content repeatability	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)
Moisture content readability	0,001%	0,001%	0,001%
Drying temperature range	Max 160 °C	Max 160 °C	Max 250 °C
<b>Physical parameters</b>			
Leveling system	semi-automatic - LevelSENSING	semi-automatic - LevelSENSING	semi-automatic - LevelSENSING
Display	10" graphic colour touchscreen	10" graphic colour touchscreen	10" graphic colour touchscreen
Weighing chamber	automatic	automatic	automatic
Maximum sample height	20 mm	20 mm	20 mm
Weighing pan dimensions	ø90, h= 8 mm	ø90, h= 8 mm	ø90, h= 8 mm
Packaging dimensions	540x610x470 mm	540x610x470 mm	540x610x470 mm
Net weight	5,3 kg	5,3 kg	5,3 kg
Gross weight	6,8 kg	6,8 kg	6,8 kg
<b>Construction</b>			
Protection class	IP 43	IP 43	IP 43
<b>Features of use</b>			
Display mode	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC
Drying method	4 drying profiles (standard, fast, step, mild)	4 drying profiles (standard, fast, step, mild)	4 drying profiles (standard, fast, step, mild)
Finish mode	4 modes (automatic, manual, time-defined, user-defined)	4 modes (automatic, manual, time-defined, user-defined)	4 modes (automatic, manual, time-defined, user-defined)
Additional functions	sample traceability	sample traceability	sample traceability
<b>Communication interface</b>			
Communication interface	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
<b>Electrical parameters</b>			
Power supply	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz
Power consumption	6 W	6 W	6 W
Heating module power	450 W	450 W	450 W
<b>Environmental conditions</b>			
Operating temperature	+10 ÷ +40 °C	+10 ÷ +40 °C	+10 ÷ +40 °C
<b>SOP – metrological tests</b>			
Mass indication control	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)
Internal adjustment	For .IC models only, GLP report	For .IC models only, GLP report	For .IC models only, GLP report
External adjustment	For all models, GLP report	For all models, GLP report	For all models, GLP report
Drying temperature control	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)
Moisture content indication control	Certified MV Test Set	Certified MV Test Set	Certified MV Test Set
<b>Adjustment</b>			
Internal / External adjustment	Depending on the type of moisture analyzer, GLP report	Depending on the type of moisture analyzer, GLP report	Depending on the type of moisture analyzer, GLP report

1 Barcode scanners, available as weighing instrument accessory, communicate with the instrument via RS232 interface exclusively.

# Datasheet

	MA 200/1.5Y.IC Moisture Analyzer	MA 200/1.5Y.IC.NS Moisture Analyzer	MA 200/1.5Y.IC.WH Moisture Analyzer
<b>Metrological parameters</b>			
Maximum capacity [Max]	200 g	200 g	200 g
Readability [d]	0,1 mg	0,1 mg	0,1 mg
Tare range	-200 g	-200 g	-200 g
Adjustment	internal (automatic)	internal (automatic)	internal (automatic)
Maximum sample weight	200 g	200 g	200 g
Heating module	IR emitter	steel heater	halogen
Moisture content repeatability	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)
Moisture content readability	0,0001%	0,0001%	0,0001%
Drying temperature range	Max 160 °C	Max 160 °C	Max 250 °C
<b>Physical parameters</b>			
Leveling system	semi-automatic - LevelSENSING	semi-automatic - LevelSENSING	semi-automatic - LevelSENSING
Display	10" graphic colour touchscreen	10" graphic colour touchscreen	10" graphic colour touchscreen
Weighing chamber	automatic	automatic	automatic
Maximum sample height	20 mm	20 mm	20 mm
Weighing pan dimensions	ø90, h= 8 mm	ø90, h= 8 mm	ø90, h= 8 mm
Packaging dimensions	540x610x470 mm	540x610x470 mm	540x610x470 mm
Net weight	5,3 kg	5,3 kg	5,3 kg
Gross weight	6,8 kg	6,8 kg	6,8 kg
<b>Construction</b>			
Protection class	IP 43	IP 43	IP 43
<b>Features of use</b>			
Display mode	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC
Drying method	4 drying profiles (standard, fast, step, mild)	4 drying profiles (standard, fast, step, mild)	4 drying profiles (standard, fast, step, mild)
Finish mode	4 modes (automatic, manual, time-defined, user-defined)	4 modes (automatic, manual, time-defined, user-defined)	4 modes (automatic, manual, time-defined, user-defined)
Additional functions	sample traceability	sample traceability	sample traceability
<b>Communication interface</b>			
Communication interface	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
<b>Electrical parameters</b>			
Power supply	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz
Power consumption	6 W	6 W	6 W
Heating module power	450 W	450 W	450 W
<b>Environmental conditions</b>			
Operating temperature	+10 ÷ +40 °C	+10 ÷ +40 °C	+10 ÷ +40 °C
<b>SOP – metrological tests</b>			
Mass indication control	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)
Internal adjustment	For .IC models only, GLP report	For .IC models only, GLP report	For .IC models only, GLP report
External adjustment	For all models, GLP report	For all models, GLP report	For all models, GLP report
Drying temperature control	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)
Moisture content indication control	Certified MV Test Set	Certified MV Test Set	Certified MV Test Set
<b>Adjustment</b>			
Internal / External adjustment	Depending on the type of moisture analyzer, GLP report	Depending on the type of moisture analyzer, GLP report	Depending on the type of moisture analyzer, GLP report

1 Barcode scanners, available as weighing instrument accessory, communicate with the instrument via RS232 interface exclusively.

# Datasheet

	MA 210.5Y.IC Moisture Analyzer	MA 210.5Y.IC.NS Moisture Analyzer	MA 210.5Y.IC.WH Moisture Analyzer
<b>Metrological parameters</b>			
Maximum capacity [Max]	210 g	210 g	210 g
Readability [d]	1 mg	1 mg	1 mg
Tare range	-210 g	-210 g	-210 g
Adjustment	internal (automatic)	internal (automatic)	internal (automatic)
Maximum sample weight	210 g	210 g	210 g
Heating module	IR emitter	steel heater	halogen
Moisture content repeatability	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)
Moisture content readability	0,001%	0,001%	0,001%
Drying temperature range	Max 160 °C	Max 160 °C	Max 250 °C
<b>Physical parameters</b>			
Leveling system	semi-automatic - LevelSENSING	semi-automatic - LevelSENSING	semi-automatic - LevelSENSING
Display	10" graphic colour touchscreen	10" graphic colour touchscreen	10" graphic colour touchscreen
Weighing chamber	automatic	automatic	automatic
Maximum sample height	20 mm	20 mm	20 mm
Weighing pan dimensions	ø90, h= 8 mm	ø90, h= 8 mm	ø90, h= 8 mm
Packaging dimensions	540×610×470 mm	540×610×470 mm	540×610×470 mm
Net weight	5,4 kg	5,4 kg	5,4 kg
Gross weight	6,9 kg	6,9 kg	6,9 kg
<b>Construction</b>			
Protection class	IP 43	IP 43	IP 43
<b>Features of use</b>			
Display mode	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC	%MC, %DC, %ATRO MC, %ATRO DC, g, g/kg MC, g/kg DC, -%MC
Drying method	4 drying profiles (standard, fast, step, mild)	4 drying profiles (standard, fast, step, mild)	4 drying profiles (standard, fast, step, mild)
Finish mode	4 modes (automatic, manual, time-defined, user-defined)	4 modes (automatic, manual, time-defined, user-defined)	4 modes (automatic, manual, time-defined, user-defined)
Additional functions	sample traceability	sample traceability	sample traceability
<b>Communication interface</b>			
Communication interface	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
<b>Electrical parameters</b>			
Power supply	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz
Power consumption	6 W	6 W	6 W
Heating module power	450 W	450 W	450 W
<b>Environmental conditions</b>			
Operating temperature	+10 ÷ +40 °C	+10 ÷ +40 °C	+10 ÷ +40 °C
<b>SOP – metrological tests</b>			
Mass indication control	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)	External mass standard 50 g, 100 g, 200 g (depending on the type of moisture analyzer)
Internal adjustment	For .IC models only, GLP report	For .IC models only, GLP report	For .IC models only, GLP report
External adjustment	For all models, GLP report	For all models, GLP report	For all models, GLP report
Drying temperature control	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)	One- or two-point, depending on the drying profile (equipment: GT105k-12/Z Control Thermometer)
Moisture content indication control	Certified MV Test Set	Certified MV Test Set	Certified MV Test Set
<b>Adjustment</b>			
Internal / External adjustment	Depending on the type of moisture analyzer, GLP report	Depending on the type of moisture analyzer, GLP report	Depending on the type of moisture analyzer, GLP report

1 Barcode scanners, available as weighing instrument accessory, communicate with the instrument via RS232 interface exclusively.



## Accessories

Antivibration Tables  
Moisture analyzer accessories  
Additional modules  
Barcode scanners  
USB Hubs  
Receipt Printer

Fingerprint Reader  
Protective cover for balances  
RS 232, RS 485 cables  
RS 232 cables (scale - printer)  
RS 232 – RS 485 Converter

## Software

E2R System  
Label Editor R02  
Scales Editor 2.1

RAD-KEY  
RADWAG Remote Desktop  
RADWAG Development Studio

## Device dimensions

MA 210.5Y.IC.WH Moisture Analyzer, MA 110.5Y.IC Moisture Analyzer, MA 50.5Y.IC.WH Moisture Analyzer, MA 50/1.5Y.IC.NS Moisture Analyzer, MA 210.5Y.IC Moisture Analyzer, MA 200/1.5Y.IC.NS Moisture Analyzer, MA 200/1.5Y.IC.WH Moisture Analyzer, MA 50.5Y.IC.NS Moisture Analyzer, MA 50/1.5Y.IC.WH Moisture Analyzer, MA 50.5Y.IC Moisture Analyzer, MA 50/1.5Y.IC Moisture Analyzer, MA 110.5Y.IC.WH Moisture Analyzer, MA 210.5Y.IC.NS Moisture Analyzer, MA 110.5Y.IC.NS Moisture Analyzer, MA 200/1.5Y.IC Moisture Analyzer

