



# Overhead track scale approvable

2922

- ▶ Approvable, class III
- ▶ Each tube track system is installed with 60 mm  $\varnothing$  tube diameter
- ▶ Configuration of aluminum load cell: Protection class IP 65
- ▶ Configuration of stainless steel load cell: Protection class IP 68/69K
- ▶ Corrosion protection due to hot-dip galvanizing and 1.4301 stainless steel



## Features

---

- ▶ Approvable, class III
- ▶ Each tube track system is installed with 60 mm  $\varnothing$  tube diameter
- ▶ Configuration of aluminum load cell: Protection class IP 65
- ▶ Configuration of stainless steel load cell: Protection class IP 68/69K
- ▶ Corrosion protection due to hot-dip galvanizing of the carrier material
- ▶ 10 m measurement cable
- ▶ Can be combined with all approvable Soehnle Professional terminals

## Products

Order number Variation	Approvable	Division g	Maximum load kg	Model	Weighing rail length mm
<b>2922.50.002</b> Overhead track scale	Yes	50	150	Aluminium load cell	200
<b>2922.51.002</b> Overhead track scale	Yes	100	300	Aluminium load cell	200
<b>2922.55.002</b> Overhead track scale	Yes	50	150	Stainless steel load cell	200
<b>2922.56.002</b> Overhead track scale	Yes	100	300	Stainless steel load cell	200
<b>2922.60.002</b> Overhead track scale	Yes	100	300	Aluminium load cell	600
<b>2922.61.002</b> Overhead track scale	Yes	200	600	Aluminium load cell	600
<b>2922.65.002</b> Overhead track scale	Yes	100	300	Stainless steel load cell	600
<b>2922.66.002</b> Overhead track scale	Yes	200	600	Stainless steel load cell	600
<b>2922.70.002</b> Overhead track scale	Yes	100	300	Aluminium load cell	800
<b>2922.71.002</b> Overhead track scale	Yes	200	600	Aluminium load cell	800
<b>2922.75.002</b> Overhead track scale	Yes	100	300	Stainless steel load cell	800
<b>2922.76.002</b> Overhead track scale	Yes	200	600	Stainless steel load cell	800
<b>2922.80.002</b> Overhead track scale	Yes	100	300	Aluminium load cell	1.000
<b>2922.81.002</b> Overhead track scale	Yes	200	600	Aluminium load cell	1.000
<b>2922.85.002</b> Overhead track scale	Yes	100	300	Stainless steel load cell	1.000
<b>2922.86.002</b> Overhead track scale	Yes	200	600	Stainless steel load cell	1.000

## Accessories

Order number	Description
Variation	
<b>2510.22.004</b>	Track mount, corrosion-protected
<b>2510.22.00x</b>	Ceiling mounting max. 530 mm, corrosion-protected
<b>2550.05.002</b>	Plug-in interface with ID chip installed, approvable section point between scale and display
<b>2503.50.001</b>	Plastic insert for smooth movement of hanging parts on the scale for 200 mm weighing track length, aluminum load cell
<b>2503.50.002</b>	Plastic insert for smooth movement of hanging parts on the scale for 200 mm weighing track length, stainless steel load cell
<b>2503.50.003</b>	Plastic insert for smooth movement of hanging parts on the scale for 600 mm weighing track length
<b>2503.50.004</b>	Plastic insert for smooth movement of hanging parts on the scale for 800 mm weighing track length
<b>2503.50.005</b>	Plastic insert for smooth movement of hanging parts on the scale for 1.000 mm weighing track length